

CONDUCTIVITY METER

Model : YK-43CD

ISO-9001, CE, IEC1010

FEATURES



- * Separate electrode, easy operation.
- * The portable conductivity meter provides fast, accurate readings, with digital readability and the convenience of a remote probe separately.
- * Multi measuring ranges: 1.999 mS and 19.99 mS.
- * LCD display for low power consumption & clear read-out even in bright ambient light condition.
- * * Water resistance on the front panel.
- * All function keys are used the rubber button.
- * Data hold.
- * Used the durable, long-lasting components, including a strong, light weight ABS-plastic housing case.
- * Built-in Low battery indicator.
- * Wide applications: water conditioning, aquariums, beverage, fish hatcheries, food processing, photography, laboratory, paper industry, plating industry, quality control, school & college.



Lutron

LUTRON ELECTRONIC

The Art of Measurement

CONDUCTIVITY METER

Model : YK-43CD

FEATURES

- * Separate electrode, easy operation.
- * The portable conductivity meter provides fast, accurate readings, with digital readability and the convenience of a remote probe separately.
- * Multi measuring ranges: 1.999 mS, 19.99 mS.
- * LCD display for low power consumption & clear read-out even in bright ambient light condition.
- * Water resistance on the front panel.
- * All function keys are used the rubber button.
- * Data hold.
- * Used the durable, long-lasting components, including a strong, light weight ABS-plastic housing case.
- * Built-in Low battery indicator.
- * Wide applications: water contioning, aquariums, beverage, fish hatcheries, food processing, photography, laboratory, paper industry, plating industry, quality control, school & college.

SPECIFICATIONS

Display	Large LCD display, 21.5 mm digit height. Max. display count no. 1999.
Measurement & Range	2 ranges, 1.999 mS, 19.99 mS.
Resolution	0.001 mS for 1.999 mS range. 0.01 mS for 19.99 mS range. <i>* mS - milli Simens</i>
Accuracy ($23 \pm 5 \text{ }^\circ\text{C}$)	$\pm (3\% \text{ F.S.} + 1 \text{ d})$ <i>* F.S. - Full scale</i>
Sampling Time	Approx. 0.4 second.
Over Range Indicator	Display shows " 1 ".
Data Hold	To feeze the measured pH value on the display.
Temperature Compensation	Automatic, 0 to 50 $^\circ\text{C}$ (32 to 122 $^\circ\text{F}$).
Operating Temp.	0 to 50 $^\circ\text{C}$ (32 to 122 $^\circ\text{F}$).
Operating Humidity	Max. 80% RH.
Power Supply	DC 9V battery (heavy duty type). 006P, MN1604(PP3) or equivalent.
Power Current	Approx. DC 5 mA.
Weight	270 g/0.60 LB (w/battery & electrode).
Dimension	<i>Meter :</i> 200 x 68 x 30 mm (7.9 x 2.7 x 1.2 inch). <i>Electrode :</i> Round, 22 mm Dia. x 120 mm length.
Accessories Included	Operation Manual..... 1 PC. Conductivity electrode..... 1 PC.
Optional Accessories	1.413 mS calibration solution..... CD-14 Hard Carrying Case..... CA-06 Soft Carrying Case with sash..... CA-05A

* Appearance and specifications listed in this brochure are subject to change without notice.

0906-YK43CD