pH ELECTRODE

Model: PE-03, PE-11, PE-01 *ISO-9001, CE, IEC1010*

PE-06HDA, PE-04HD, PE-03K7, PE-21

LUTRON ELECTRONIC



The Art of Measurement

full line

pH ELECTRODE

pH ELECTRODE	* General purpose, laboratory and field usage.
Model : PE-03	* 12.3 mm dia. x 160 mm.
	* Epoxy body, 1 - 13 pH.
pH ELECTRODE	* General purpose, laboratory and field usage.
Model : PE-11	* 10 mm dia. x 130 mm.
	* Epoxy body.
	* 1 - 13 pH. (0 - 14 pH typical)
pH ELECTRODE	* Professional, laboratory and field usage.
Model: PE-01	* 9.5 mm dia. x 130 mm.
	* Epoxy body.
	* 0 - 14 pH.
SPEAR TIP	* The " Spear Tip pH electrode " is perfect for those pH
pH ELECTRODE	measurements in applications where sample piercing
	is required. Meat, sausage and cheese are ideal
Model: PE-06HDA	applications. The electrodefeatures a very durable
PE-04HD	glass measuring spear packaged in a rugged virtually
	unbreakable epoxy body.
	* Range : 0 to 14 pH (PE-04HD)
	* Range: 1 to 13 pH (PE-06HDA)
pH ELECTRODE + Temp. PROBE	* One kit combine of pH electrode PE-03 and Temp.
(combination kit of pH electrode)	probe TP-07 as a whole unit.
	* Easy operation for the pH measurement under
Model: PE-03K7	the ATC (Automatic Temp. Compensation).
	* Available for PH-208, PH-207, PH-207HA, PH-221,
	PH-221E, YK-2005WA., PH-230SD. WA-2017SD,
	WA-2015, BPH-231, PH-224S, YK-2001PHA.

^{*} Appearance and specifications listed in this brochure are subject to change without notice. 1809-PHELECTRODE